

PRIZMA LED

- Behuizing van aluminium, grijs gespoten
- Prismatische open heldere reflector van polycarbonaat
- Inclusief bevestigingshaak



Artikel	Type	Uitvoering	Ø X H	Lumen	Groep
7102005	PRIZMALED31.3	34W 3000K	410 x 425	3965	2900
7102006	PRIZMALED48.3	51W 3000K	410 x 425	5546	
7102007	PRIZMALED77.3	84W 3000K	510 x 540	8647	
7102008	PRIZMALED98.3	107W 3000K	510 x 540	10525	
7102009	PRIZMALED31.4	34W 4000K	410 x 425	4088	
7102010	PRIZMALED48.4	51W 4000K	410 x 425	5718	
7102011	PRIZMALED77.4	84W 4000K	510 x 540	8915	
7102014	PRIZMALED98.4	107W 4000K	510 x 540	10851	
7102003	PRIZMALED PC COVER	Ø410mm			
7102004	PRIZMALED PC COVER	Ø510mm			

Specificaties

Aansluitspanning	220-240V
CRI	>80
Type LED	OSRAM COB
Levensduur	50.000 uur
Lichtterugval	L80B50
MacAdam steps	<4
Powerfactor driver	0,95
Dimbaar	Optioneel
Omgevingstemperatuur	-20°C tot +50°C
Stralingshoek	80°
IP	65
IK	02

Garantie

3 jaar

Dutch Light Trading B.V.

Optioneel

Driver DALI DIM

+ Bruto € 89,00